

SuperKlean™

Environmentally Exceptional Washdown Products

DuraFlow “Mini” Spray Nozzles

- Small, compact design.
- Fully insulated.
- 304 stainless steel construction.
- 1/2” female NPT inlet.

DM150S

Inlet/Outlet Diameter: ½ ” NPT

Nozzle Body: Stainless Steel. Epoxy resin coated.

Cartridge: Stainless Steel

Weight: 1.25 lbs

Recommended Operative Conditions

Maximum Pressure: 150 PSI

Maximum Temperature: 200 °F (93 °C)

Inlet Pressure (PSIG) Flow Rate (GPM)

Standard

25	4.39
50	6.54
75	8.18
100	9.56
125	10.83
150	11.89

High Flow

25	4.39
50	6.54
75	8.18
100	9.56
125	10.83
150	11.89



SuperKlean™

Environmentally Exceptional Washdown Products

DuraFlow "Mini" Spray Nozzles

Part #	Description
2-DMS	DuraFlow "Mini" lever, stainless steel. Plastic dip
3-DM	DuraFlow "Mini" nozzle lever bolt, stainless steel
4-DMDB	Nozzle cover, dark blue
4-DMR	Nozzle cover, red
4-DMW	Nozzle cover, white
7-DMS	Cartridge or "barrel assembly," 304 stainless steel, contains all working parts

2-DMS



7-DMS



3-DM



4-DMDB



4-DMR



4-DMW

