

SuperKlean™

Environmentally Exceptional Washdown Products

DuraFlow Spray Nozzles

- Front trigger guard cover designed to prevent accidental spray.
- Trigger lock mechanism built in.
- Quick connect receptacle for accessories.
- Compatible with DuraWand.

DH150S

Inlet/Outlet Diameter: ½" NPT

Nozzle Body: Stainless Steel. Epoxy resin coated.

Cartridge: Stainless Steel

Weight: 1.7 lbs

Recommended Operative Conditions

Maximum Pressure: 150 PSI

Maximum Temperature: 200 °F (93 °C)

Inlet Pressure (PSIG) Flow Rate (GPM)

Standard Flow*

| | |
|-----|------|
| 25 | 2.93 |
| 50 | 3.86 |
| 75 | 4.91 |
| 100 | 5.78 |
| 125 | 6.71 |
| 150 | 7.19 |

High Flow

| | |
|-----|-------|
| 25 | 4.39 |
| 50 | 6.54 |
| 75 | 8.18 |
| 100 | 9.56 |
| 125 | 10.83 |
| 150 | 11.89 |

*Standard flow rates can be achieved with the purchase of flow restrictor adapter (Part: 8-FR-NPT)



SuperKlean™

Environmentally Exceptional Washdown Products

DuraFlow Spray Nozzles

| Part # | Description |
|--------|---|
| 2-DHS | DuraFlow lever, stainless steel. Plastic dip |
| 3-DH | DuraFlow nozzle lever bolt, stain- less steel |
| 4-DDB | Nozzle cover, dark blue |
| 4-DR | Nozzle cover, red |
| 4-DW | Nozzle cover, white |
| 7-DS | Cartridge or "barrel assembly," 304 stainless steel, contains all working parts |

2-DHS



7-DS



3-DH



4-DDB



4-DR



4-DW

